NSN 5930-00-910-5844

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-910-5844

Overall Length:
1.250 inches
Overall Height:
0.440 inches
Overall Width:
0.401 inches
Body Length:
0.776 inches
Body Width:
0.401 inches
Body Height:
0.251 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.000 inches
Longest Horizontal Distance Between Mounting Centers:
1.000 inches
Tempurature Sensing Element Type:
Immersion well
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 200.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.5 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+35.00/+45.00 actuation point degrees fahrenheit and +35.00/+45.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

40.00 actuation point degrees fahrenheit and 0.00 deactuation point degrees fahrenheit

NSN 5930-00-910-5844

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:	Contact	Voltage	Rating	In	Volts
----------------------------------	---------	---------	--------	----	-------

115.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0