

View Online at <https://aerobasegroup.com/nsn/5930-00-911-2743>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.641 inches

Overall Height:

1.531 inches

Overall Width:

1.312 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

2.125 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

60.0 degrees 2nd actuator

Switch Actuator Stop Device Type:

Fixed stop-breakoff tab 1st actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at sea level

Special Features:

Variable resistor p/n p50439080 supplied by lavoie laboratories inc

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material:

Silver and gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0