

View Online at <https://aerobasegroup.com/nsn/5930-00-911-2743>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.641 inches

**Overall Height:**

1.531 inches

**Overall Width:**

1.312 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

2.125 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 9: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

60.0 degrees 2nd actuator

**Switch Actuator Stop Device Type:**

Fixed stop-breakoff tab 1st actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load ac at sea level

**Special Features:**

Variable resistor p/n p50439080 supplied by lavoie laboratories inc

**Precious Material And Location:**

Contact surfaces silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0