

View Online at <https://aerobasegroup.com/nsn/5930-00-911-2776>

Thread Class:

2a single mounting facility

Thread Length:

0.344 inches single mounting facility

Overall Length:

2.812 inches

Overall Height:

1.531 inches

Overall Width:

1.312 inches

Shaft Diameter:

0.265 inches 1st actuator

Shaft Length:

1.000 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 2nd actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees 2nd actuator

Detent Rotational Torque Range:

+18.000/+30.000 inch-ounces 2nd actuator

Switch Actuator Stop Device Type:

Fixed stop 2nd actuator

Contact Load Current Rating:

450.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Clip surfaces gold and clips and rotor blades silver

Precious Material:

Gold and silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0