

View Online at <https://aerobasegroup.com/nsn/5930-00-911-2777>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

9.250 inches

**Overall Height:**

2.312 inches

**Overall Width:**

1.969 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.125 inches single actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.000 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 5th section rear

**Throw Quantity:**

8 5th section front

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 5th section

**Switch Actuator Indexing Position Quantity:**

16 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Clip

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

20.0 degrees 1st actuator

**Detent Rotational Torque Range:**

+60.000/+85.000 inch-ounces 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

450.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Clip surfaces gold and clips and rotor blades silver

**Precious Material:**

Gold and silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0