

View Online at <https://aerobasegroup.com/nsn/5930-00-911-6260>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.093 inches

Overall Height:

1.578 inches

Overall Width:

1.422 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.718 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 2nd section front

Throw Quantity:

2 2nd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

225.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section front

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Detent Rotational Torque Range:

+1.500/+6.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0