

View Online at <https://aerobasegroup.com/nsn/5930-00-911-9910>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.000 inches

Overall Height:

6.219 inches

Overall Width:

2.812 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

6.000 inches

Bulb Diameter:

1.125 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

150.0 degrees fahrenheit

Mounting Method:

Bracket

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

-10.00/+50.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0