

View Online at <https://aerobasegroup.com/nsn/5930-00-912-1471>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.201 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.032 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

1.313 inches single actuator

Individual Section Quantity:

5

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

2.297 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

15 each section periphery

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 2nd mounting facility

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

15 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0