# NSN 5930-00-912-1494

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-912-1494

# **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Dustproof and oiltight and watertight

# **Case Material:**

Metal

## Actuator Length:

1.250 inches

### Actuator Style:

Roller arm

### Actuator Roller Diameter:

1.000 inches

## Actuator Roller Width:

0.250 inches

## **Housing Height:**

2.100 inches

# Housing Length:

4.940 inches

# Housing Width:

2.310 inches

# Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.220 inches

# Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.810 inches

# Maximum Voltage Rating In Volts:

600.0 ac

# Inclosure Type:

Fully enclosed

# **Features Provided:**

Actuator seal

### **Actuator Movement:**

11.0 differential degrees and 17.0 pretravel degrees

# Contact Load Current Rating At Maximum Rated Voltage:

1.200 amperes resistive ac

### **Special Features:**

Model ponl is a special pre-wired switch

# **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 5930-00-912-1494

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

