

View Online at <https://aerobasegroup.com/nsn/5930-00-912-3344>

Body Style:

Bushing mount

Overall Length:

Between 1.625 inches and 1.635 inches

Overall Height:

2.990 inches

Overall Width:

Between 1.305 inches and 1.335 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 1.625 inches and 1.635 inches

Body Width:

Between 1.305 inches and 1.335 inches

Actuator Style:

Round

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 1.335 inches and 1.365 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 12.000 amperes inductive dc and 6.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0