NSN 5930-00-912-3934

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-912-3934

0.375 inches single mounting facility Overall Length: 2.125 inches Overall Height: 1.875 inches Overall Width: 1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length:
2.125 inches Overall Height: 1.875 inches Overall Width: 1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
Overall Height: 1.875 inches Overall Width: 1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
1.875 inches Overall Width: 1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
Overall Width: 1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
1.563 inches First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
First Flat Length: 0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
0.313 inches single actuator Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
Flat Height: 0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
0.218 inches single actuator Shaft Diameter: 0.250 inches single actuator
Shaft Diameter: 0.250 inches single actuator
0.250 inches single actuator
•
Shaft Length:
0.875 inches single actuator
Individual Section Quantity:
2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
115.0 dc at sea level
Shaft Flat/slot Angular Location:
150.0 degrees from nonturn device single actuator
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator

NSN 5930-00-912-3934

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

0.5 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0