

View Online at <https://aerobasegroup.com/nsn/5930-00-913-0735>

Thread Class:

3b single pressure connection

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

160.0 degrees fahrenheit

Mounting Method:

Base

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

6000.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1450.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

440.0 ac at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0