

View Online at <https://aerobasegroup.com/nsn/5930-00-913-0735>

**Thread Class:**

3b single pressure connection

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

3.100 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

160.0 degrees fahrenheit

**Mounting Method:**

Base

**Thread Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

3000.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Sensing Element Burst Pressure:**

6000.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

3.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

1450.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

440.0 ac at sea level single voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Gas

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0