NSN 5930-00-913-2982

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-913-2982

| Body Style: |
|---|
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Waterproof |
| Overall Length: |
| 1.063 inches |
| Body Diameter: |
| 0.562 inches |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.875 inches |
| Switch Actuator Quantity: |
| 6 |
| Actuator Diameter: |
| 0.312 inches |
| Actuator Height: |
| 0.312 inches |
| Maximum Voltage Rating In Volts: |
| 120.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.500 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive ac |
| Thread Series Designator: |
| Un |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-00-913-2982

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0