

View Online at <https://aerobasegroup.com/nsn/5930-00-913-4844>

Hazardous Locations/environmental Protection:

Dusttight and moisture proof

Overall Length:

6.391 inches

Body Diameter:

0.375 inches

Body Length:

5.531 inches

Overall Diameter:

2.219 inches

Distance Between Mounting Facility Centers:

1.688 inches

Capillary Tube Length:

48.000 inches

Bulb Length:

1.438 inches

Bulb Diameter:

0.375 inches

End Application:

Mc-7 air compressor 93234

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded stud

Features Provided:

Tubing end seal connection

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Clip

Contact Load Current Rating:

9.3 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+250.00 actuation point degrees fahrenheit and +100.00/+250.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point pointer with scale and external actuation point pointer with scale

Contact Voltage Rating In Volts:

14.8 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0