

View Online at <https://aerobasegroup.com/nsn/5930-00-914-6450>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.101 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.281 inches

Actuator Free Position Height:

0.243 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

3.5 ounces

Actuator Movement:

0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

Special Features:

Reset button

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0