## NSN 5930-00-914-6450

Sensitive Switch - Page 1 of 2

**Body Style:** 

**Special Features:** 

Reset button



View Online at https://aerobasegroup.com/nsn/5930-00-914-6450

Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.520 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.101 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.312 inches
Actuator Length:
0.250 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.281 inches
Actuator Free Position Height:
0.243 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
3.5 ounces
Actuator Movement:
0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

## NSN 5930-00-914-6450

Sensitive Switch - Page 2 of 2



T	ermina	ΙTν	/ne	Δnd	Out	antity:	
ı	emma		v ne	Allu	wu.	antutv.	

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0