NSN 5930-00-914-6461

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-914-6461

Body Style:
Bushing mounted
Overall Length:
1.875 inches
Overall Height:
0.563 inches
Overall Width:
0.563 inches
Body Diameter:
0.563 inches
Bushing Length:
0.625 inches
Body Length:
1.110 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
0.765 inches
Actuator Roller Diameter:
0.250 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Hwkeye e-2c/c-2a aircraft
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:

Between 0.030 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc

NSN 5930-00-914-6461 Sensitive Switch - Page 2 of 2



Thread Series Designator:
Uns
Terminal Type And Quantity
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0