NSN 5930-00-914-7441

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-914-7441 **Body Style:** Hole mounted **Actuator Style:** Roller plunger **Actuator Free Position Height:** 2.078 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.190 inches **Housing Height:** 1.750 inches **Housing Length:** 3.040 inches **Housing Width:** 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.625 inches **Maximum Voltage Rating In Volts:** 480.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 13 **Thread Size:** 0.500 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** 13.0 ounces **Actuator Movement:** Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 15.000 amperes resistive ac **Thread Series Designator:** Unc

Terminal Type And Quantity:

3 screw

NSN 5930-00-914-7441

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0