

View Online at <https://aerobasegroup.com/nsn/5930-00-916-5197>

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.975 inches

First Flat Length:

0.468 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.247 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

2.000 inches

Nonturn Device Radius:

0.372 inches at 12: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

18 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

18 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0