NSN 5930-00-916-5537

Pressure Switch - Page 1 of 2

Thread Class:

Pressure Connector Type:

Plain, threaded internal all connections



View Online at https://aerobasegroup.com/nsn/5930-00-916-5537

2b all pressure connection
Inside Diameter:
0.250 inches all connections
Overall Length:
3.000 inches
Overall Height:
4.250 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Longest Horizontal Distance Between Mounting Centers:
2.500 inches
Longest Vertical Distance Between Mounting Centers:
2.500 inches
Pressure Switch Type:
Gage
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
18 all pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
4.0 amperes resistive load second voltage and 0.2 amperes inductive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
15.00 actuation point inches of mercury
Contact Voltage Rating In Volts:
480.0 ac at sea level first voltage

NSN 5930-00-916-5537

Pressure Switch - Page 2 of 2



Frequency In Hertz:
50.0 first voltage and 60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Npt all pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0