

View Online at <https://aerobasegroup.com/nsn/5930-00-916-7902>

Hazardous Locations/environmental Protection:

Hermetically sealed

Unthreaded Mounting Hole Diameter:

0.190 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

3.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.500 inches single mounting facility

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

50.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Terminal Type:

Connector, receptacle

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load dc at sea level

Special Features:

Solenoid operated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0