

View Online at <https://aerobasegroup.com/nsn/5930-00-916-7902>

**Hazardous Locations/environmental Protection:**

Hermetically sealed

**Unthreaded Mounting Hole Diameter:**

0.190 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

3.875 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches single mounting facility

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

50.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Terminal Type:**

Connector, receptacle

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load dc at sea level

**Special Features:**

Solenoid operated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0