## NSN 5930-00-916-7904

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-916-7904

**Thread Class:** 2a single mounting facility **Overall Length:** 3.625 inches **Overall Height:** 2.781 inches **Overall Width:** 2.469 inches First Flat Length: 0.750 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.125 inches single actuator **Individual Section Quantity:** 6 **Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 1.625 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.625 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 3 each section rear **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 120.0 dc at sea level **Mounting Facility Pattern:** 

3 single actuator

Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 

## **NSN 5930-00-916-7904**Rotary Switch - Page 2 of 2



Shart Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0