NSN 5930-00-916-7926

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-916-7926

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and oiltight and watertight
Switch Actuator Quantity:
2
Actuator Length:
1.560 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.100 inches
Housing Length:
4.950 inches
Housing Width:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.220 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.810 inches
Maximum Voltage Rating In Volts:
600.0 ac
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
3 pole, single throw, double make, both positions maintained single switch unit
Switch Actuating Force:
45.0 inch-ounces
Actuator Movement:
11.0 differential degrees and 17.0 pretravel degrees
Contact Load Current Rating At Maximum Rated Voltage:
1.200 amperes resistive ac
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5930-00-916-7926

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0