# NSN 5930-00-916-7926

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-916-7926

### **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Dustproof and oiltight and watertight

# Switch Actuator Quantity:

2

## Actuator Length:

1.560 inches

#### Actuator Style:

Roller arm

#### Actuator Roller Diameter:

0.750 inches

#### Actuator Roller Width:

0.250 inches

#### **Housing Height:**

2.100 inches

## Housing Length:

4.950 inches

#### Housing Width:

2.310 inches

### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.220 inches

### Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.810 inches

# Maximum Voltage Rating In Volts:

600.0 ac

#### Inclosure Type:

Fully enclosed

#### Nonpile-up Contact Arrangement:

3 pole, single throw, double make, both positions maintained single switch unit

#### Switch Actuating Force:

45.0 inch-ounces

#### Actuator Movement:

11.0 differential degrees and 17.0 pretravel degrees

#### Contact Load Current Rating At Maximum Rated Voltage:

1.200 amperes resistive ac

### **Terminal Type And Quantity:**

6 screw

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-916-7926

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

