

View Online at <https://aerobasegroup.com/nsn/5930-00-916-7975>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

Between 0.490 inches and 0.510 inches

**Actuator Roller Width:**

Between 0.115 inches and 0.135 inches

**Housing Length:**

Between 2.498 inches and 2.502 inches

**Housing Width:**

Between 0.611 inches and 0.632 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

Between 1.553 inches and 1.573 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 1.865 inches and 1.885 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

Between 88.0 ounces and 152.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 screw

**Specification Data:**

81349-mils8805/53 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0