

View Online at <https://aerobasegroup.com/nsn/5930-00-916-7975>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.490 inches and 0.510 inches

Actuator Roller Width:

Between 0.115 inches and 0.135 inches

Housing Length:

Between 2.498 inches and 2.502 inches

Housing Width:

Between 0.611 inches and 0.632 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

Between 1.553 inches and 1.573 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 1.865 inches and 1.885 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

Between 88.0 ounces and 152.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 screw

Specification Data:

81349-mils8805/53 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0