

View Online at <https://aerobasegroup.com/nsn/5930-00-917-2011>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.375 inches

Overall Height:

4.156 inches

Overall Width:

2.688 inches

Capillary Tube Length:

300.000 inches

Bulb Length:

3.625 inches

Bulb Diameter:

0.688 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

150.0 degrees fahrenheit

Mounting Method:

Bracket

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

-10.00/+50.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Frequency In Hertz:

60.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0