NSN 5930-00-917-3601

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-917-3601 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Moisture resistant and salt spray resistant **Overall Length:** 3.890 inches **Overall Height:** 1.030 inches **Overall Width:** 1.030 inches **Body Diameter:** 1.030 inches **Bushing Length:** 1.300 inches **Body Length:** 1.715 inches **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.375 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac **Thread Series Designator:** Unef **Terminal Type And Quantity:** 6 wire lead

N/a

Shelf Life:

NSN 5930-00-917-3601

Push Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0