

View Online at <https://aerobasegroup.com/nsn/5930-00-917-7770>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

2.438 inches

Overall Height:

2.266 inches

Overall Width:

2.266 inches

First Flat Length:

0.406 inches single actuator

Flat Height:

0.186 inches single actuator

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.907 inches single actuator and 0.969 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.750 inches single mounting facility

Operating Temperature Range:

-40.0/+95.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section rear

Throw Quantity:

7 single section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0