

View Online at <https://aerobasegroup.com/nsn/5930-00-917-8328>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

2.485 inches

**Overall Height:**

0.688 inches

**Overall Width:**

0.688 inches

**Body Diameter:**

0.688 inches

**Bushing Length:**

1.000 inches

**Body Length:**

1.000 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.485 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.135 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0