

View Online at <https://aerobasegroup.com/nsn/5930-00-918-0404>

Thread Class:

2b single pressure connection

Thread Length:

0.500 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and dusttight and moisture proof

Overall Length:

5.750 inches

Overall Height:

10.812 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.062 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

3600.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+250.00/+3000.00 actuation point pounds per square inch gage and +250.00/+3000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Flareless, threaded external single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0