## NSN 5930-00-918-2498

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-918-2498

## Thread Class:

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## **Overall Height:**

Between 1.297 inches and 1.327 inches

#### **Overall Width:**

1.250 inches

#### Shaft Diameter:

0.250 inches single actuator

#### **Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

### Individual Section Quantity:

14

### Nonturn Device Type:

Tab at 3: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

## Thread Size:

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

#### **Precious Material And Location:**

Contact surfaces silver

#### **Precious Material:**

Silver

## Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

## Shelf Life:

N/a

# NSN 5930-00-918-2498

Rotary Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

