

View Online at <https://aerobasegroup.com/nsn/5930-00-918-3269>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

1.000 inches

Bushing Length:

0.812 inches

Body Length:

2.278 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.395 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

1.000 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0