NSN 5930-00-918-3269

Sensitive Switch - Page 1 of 2

eroBase

View Online at https://aerobasegroup.com/nsn/5930-00-918-3269

Thread Class: 2a **Body Style:** Bushing mounted Hazardous Locations/environmental Protection: Watertight **Body Diameter:** 1.000 inches **Bushing Length:** 0.812 inches **Body Length:** 2.278 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.375 inches **Actuator Free Position Height:** 0.395 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal **Thread Size:** 1.000 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive dc

Thread Series Designator:

Unef

NSN 5930-00-918-3269

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0