

View Online at <https://aerobasegroup.com/nsn/5930-00-918-6138>

Thread Length:

0.422 inches single mounting facility and 0.454 inches single mounting facility

Overall Length:

Between 3.102 inches and 3.466 inches

Overall Diameter:

1.036 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes inductive load dc at sea level

Special Features:

Additional nonturn device type slotted bushing, nonturn device radius 0.170 in. Nom at 3:00 o'clock

Style Designator:

Circular wafer, bushing mount

Test Data Document:

81349-mil-s-3786/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0