## NSN 5930-00-918-6852

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-918-6852

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

Between 2.312 inches and 2.437 inches

**Overall Height:** 

Between 2.234 inches and 2.266 inches

**Overall Width:** 

Between 2.234 inches and 2.266 inches

**Shaft Diameter:** 

0.249 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.906 inches single actuator and 0.968 inches single actuator

**Individual Section Quantity:** 

1

## **Longest Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

24 single section rear

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

**Mounting Facility Pattern:** 

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:** 

24 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Turret

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

15.0 degrees single actuator

## NSN 5930-00-918-6852

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

2.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, square frame

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0