NSN 5930-00-918-7582

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-918-7582

Thread Class:
2b all threaded hole
Overall Length:
1.560 inches
Overall Height:
2.310 inches
Overall Width:
2.030 inches
Body Length:
1.560 inches
Distance Between Mounting Facility Centers:
1.380 inches
Capillary Tube Length:
60.0 inches
Bulb Length:
7.500 inches
Bulb Diameter:
0.380 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Threaded hole
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.164 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
7.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+60.00/+90.00 actuation point degrees fahrenheit and +57.50/+87.50 deactuation point degrees fahrenheit
Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

NSN 5930-00-918-7582 Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
230.0 ac at sea level first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0