NSN 5930-00-918-8367

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-918-8367

Thread Class: 2a single mounting facility Thread Length: 0.312 inches single mounting facility **Overall Length:** 2.813 inches **Overall Height:** 1.500 inches **Overall Width:** 1.359 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.375 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 3 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 300.0 highest ac voltage rating at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:**

60.0 degrees single actuator

NSN 5930-00-918-8367

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0