

View Online at <https://aerobasegroup.com/nsn/5930-00-919-1755>

Body Style:

Hole mounted

Overall Length:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.812 inches

Overall Height:

0.743 inches

Overall Width:

0.400 inches

Body Length:

0.628 inches

Body Width:

0.400 inches

Body Height:

0.300 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.100 inches

Actuator Length:

0.200 inches

Actuator Height:

0.200 inches

Actuator Width:

0.125 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

End Application:

Sturgeon class ssn (637), los angeles class ssn (688). Sh-60f carrier based helicopter. Hh-60j and hh-60h search and rescue helicopter. Phoenix air to air (aim-54) missile, all-weather anti-ship harpoon (agm-84) missile. Landing craft air cushion (lcac). An/sps-4 (v) series radar.

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 500.000 milliamperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts and terminal surfaces silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0