NSN 5930-00-919-7778

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-919-7778

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and oiltight and watertight
Actuator Length:
2.500 inches
Actuator Style:
Roller arm
Actuator Height:
1.250 inches
Actuator Roller Diameter:
1.000 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.100 inches
Housing Length:
4.940 inches
Housing Width:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Center to Center Distance between Housing Mounting Facilities Farance to Length.
4.220 inches
4.220 inches
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw Shelf Life:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw Shelf Life: N/a
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw Shelf Life: N/a
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure:
4.220 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.810 inches Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure: Demilitarization: