

View Online at <https://aerobasegroup.com/nsn/5930-00-921-6016>

Thread Class:

2a single mounting facility

Thread Length:

0.219 inches single mounting facility and 0.281 inches single mounting facility

Overall Length:

1.283 inches

Overall Height:

Between 0.978 inches and 1.102 inches

Overall Width:

Between 0.909 inches and 0.971 inches

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.500 inches single actuator

Nonturn Device Radius:

0.365 inches at 3: 00 o'clock and 0.385 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front 2 single section rear

Throw Quantity:

2 single section front 2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+0.750/+4.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load ac at sea level 200.0 milliamperes inductive load dc at sea level and 20.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Clips and rotor blades silver and clip and rotor blade surfaces gold

Precious Material:

Silver and gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0