

View Online at <https://aerobasegroup.com/nsn/5930-00-923-3640>

Thread Class:

3a single pressure connection

Overall Length:

2.280 inches

Outside Diameter:

0.312 inches single connection

Body Length:

1.812 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 175.0 degrees fahrenheit

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1125.00 pounds per square inch

Thread Size:

0.312 inches single pressure connection

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Turret

Contact Load Current Rating:

10.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+30.00 actuation point pounds per square inch and +0.00/+30.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

26.20 actuation point pounds per square inch gage and 22.40 deactuation point pounds per square inch gage and 3.80 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

110.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0