

View Online at <https://aerobasegroup.com/nsn/5930-00-923-4176>

Overall Length:

3.172 inches

Overall Height:

Between 3.797 inches and 3.983 inches

Overall Width:

1.547 inches

Mounting Slot Width:

Between 0.200 inches and 0.206 inches

Body Length:

2.891 inches

Body Width:

0.828 inches

Body Height:

1.438 inches

Capillary Tube Length:

Between 24.0 inches and 31.0 inches

Bulb Length:

5.625 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.000 inches

Longest Vertical Distance Between Mounting Centers:

1.266 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -50.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Six position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+40.00/+90.00 actuation point degrees fahrenheit and +38.00/+88.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

240.0 ac at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0