

View Online at <https://aerobasegroup.com/nsn/5930-00-923-4176>

**Overall Length:**

3.172 inches

**Overall Height:**

Between 3.797 inches and 3.983 inches

**Overall Width:**

1.547 inches

**Mounting Slot Width:**

Between 0.200 inches and 0.206 inches

**Body Length:**

2.891 inches

**Body Width:**

0.828 inches

**Body Height:**

1.438 inches

**Capillary Tube Length:**

Between 24.0 inches and 31.0 inches

**Bulb Length:**

5.625 inches

**Bulb Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches

**Longest Vertical Distance Between Mounting Centers:**

1.266 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

Between -50.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Base and slot

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Six position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+40.00/+90.00 actuation point degrees fahrenheit and +38.00/+88.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Voltage Rating In Volts:**

240.0 ac at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0