

View Online at <https://aerobasegroup.com/nsn/5930-00-924-7266>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.875 inches

**Overall Height:**

2.312 inches

**Overall Width:**

1.812 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.875 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 9: 30 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 9: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 each section rear

**Throw Quantity:**

23 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

24.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

23 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.75 amperes resistive load dc at sea level

**Precious Material And Location:**

Clips and contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0