

View Online at <https://aerobasegroup.com/nsn/5930-00-925-0093>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight

**Unthreaded Mounting Hole Diameter:**

Between 0.209 inches and 0.238 inches

**Actuator Length:**

2.120 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

0.970 inches

**Actuator Roller Diameter:**

1.000 inches

**Actuator Roller Width:**

0.310 inches

**Housing Height:**

2.280 inches

**Housing Length:**

6.310 inches

**Housing Width:**

1.910 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 3.580 inches and 3.600 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.760 inches

**Maximum Voltage Rating In Volts:**

550.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

32.0 ounces

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

15.0 pretravel degrees and 20.0 overtravel degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes inductive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0