

View Online at <https://aerobasegroup.com/nsn/5930-00-925-1652>

**Thread Length:**

0.438 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.876 inches single actuator

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

10 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0