

View Online at <https://aerobasegroup.com/nsn/5930-00-925-3617>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

8.126 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

2.938 inches single actuator

Individual Section Quantity:

10

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000-s6202-73075-1

Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 each section periphery

Throw Quantity:

3 each section periphery

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15473 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0